

**FAX TRANSMISSION****DATE:** July 27, 2010**MESSAGE TO:** Examiner Hutchins**FAX NUMBER:** 571-270-4651**FROM:** MILLER MATTHIAS & HULL

Scott E. Baxendale

**PHONE:** (312) 977-9969**Attorney Dkt. #:** 50002/40625**PAGES (Including Cover Sheet):** 3**CONTENTS:** PLEASE SEE ATTACHED.

If your receipt of this transmission is in error, please notify this firm immediately by collect call to sender at (312) 977-9902 and send the original transmission to us by return mail at the address below.

This transmission is intended for the sole use of the individual and entity to who it is addressed, and may contain information that is privileged, confidential and exempt from disclosure under applicable law. You are hereby notified that any dissemination, distribution or duplication of this transmission by someone other than the intended addressee or its designated agent is strictly prohibited.

**MILLER MATTHIAS & HULL**  
One North Franklin Street, Suite 2350  
**Telephone:** (312) 977-9902 **Facsimile:** (312) 977-9959

Fax to Examiner Hutchins @ 571-270-4651

Subject: Proposed Claims for 10/597,139

Dear, Ex. Hutchins,

Transmitted to your consideration in advance of our interview ~~and~~ are proposed amended claims. Please feel free to call me if you need any additional information. Otherwise, I will call you on Thursday at 11:00 am EDT.

Thank you,

Scott Bayardale

**PROPOSED AMENDMENTS – NOT FOR ENTRY IN THIS CASE**

Application No.: 10/597,139

Docket No.: 50002/40625

**AMENDMENTS TO THE CLAIMS**

1. (currently amended) A method of surveying drill holes comprising the steps of:  
feeding a survey tool comprising an inertial survey package disposed within a drill string into a borehole ~~on the end of a~~ while the drill string is operational to drill the borehole as part of a hole drilling operation[.];

activating the survey tool once drilling is completed[.];

withdrawing the drill string from the borehole; and

taking position readings from the survey tool as withdrawal of the drill string is temporarily halted to remove each drill rod from the drill string.

2. (previously presented) A method as claimed in claim 1, wherein the survey tool is maintained in a sleeping mode while drilling is undertaken.

3. (previously presented) A method as claimed claim in 2, wherein the survey tool is configured to sense the cessation of drilling to activate the survey tool once drilling is completed.

4. (canceled)

5. (currently amended) An apparatus for surveying drill holes using a method incorporating the steps of:

feeding a survey tool disposed within a drill string into a borehole ~~on the end of a~~ while the drill string is operational to drill the borehole as part of the hole drilling operation[.];

activating the survey tool once drilling is completed[.];

withdrawing the drill string from the borehole; and

taking position readings from the survey tool as withdrawal of the drill string is temporarily halted to remove each drill rod from the drill string, wherein the survey tool includes an inertial survey package and a power source.

6. (original) An apparatus as claimed in claim 5, wherein the survey tool also includes a data logger.

**PROPOSED AMENDMENTS – NOT FOR ENTRY IN THIS CASE**

Application No.: 10/597,139

Docket No.: 50002/40625

7. (previously presented) An apparatus as claimed in claim 5, wherein the survey tool is mounted to the drill string by a damping system arranged to isolate the survey tool from vibrations and acceleration induced in the drill string.

8. (previously presented) An apparatus as claimed in claim 5, wherein the inertial survey package is selected from the group comprising commercially known inertial survey packages, for superior characteristics of resistance to vibration and impact from a group comprising commercially known inertial survey packages.

9. (original) An apparatus as claimed in claim 8, wherein the inertial survey package is selected for superior resistance to vibration and impact when in a sleeping mode.